



ISO 9001-2008
ATR 0401



meisa®

AM65 NO-ASBESTO

COMPOSICION

El estilo AM65 es un laminado de color gris, fabricado a partir de una fibra sintética Aramídica, ligada con un compuesto a base de caucho SBR-NBR de alta calidad. De esta manera se obtiene una lamina para juntas con excepcional flexibilidad y comportamiento al corte, que añadidas a su característica de hinchamiento controlado en aceites, resulta muy apropiada para la industrial en general.

Dimensiones: 40X40, 50X50, 60X62, 75X75, 60X120, 75X150, 150X150, 120X120 pulgadas.
Espesores : 1/32, 3/64, 1/16, 3/32, 1/8, 3/16, ¼ pulgadas y especiales.

Cumple con la norma ASTM F104

PARAMETROS

AM 65

Presión Max= 100 kg/cm² Tmax= 420°C



Manufacturera e Insumos, S.A. de C.V.
Camino viejo a la estación de FFCC No. 102.
Predio San Ignacio.
C.P. 38480.
Cortazar, Gto. México.
Tel. +52 (01411) 1553531.

LOS DATOS OBTENIDOS EN ESTA HOJA TECNICA SIRVEN COMO GUIA PARA LA ELECCION DE LA LAMINA ADECUADA A LAS DIFERENTES CONDICIONES DE OPERACIÓN, INSTALACION Y USO, DE LOS CUALES NO TENEMOS INFLUENCIA POR LO TANTO LA GARANTIA SE LIMITA A LA CALIDAD DE LOS MATERIALES.





ISO 9001-2008
ATR 0401



meisa®

AM65 NO-ASBESTOS (SYNTHETIC FIBERS)

COMPOSITION

The style AM45 gray in color, this manufactured with synthetic fiber aramid, bonded rubber SBR-NBR, is used in the oil industry, petrochemical industry and process in general.

Is a sheet of gray, produced from asynthetic fibers aramid league with a compound basa rubber SBR-NBR high quality. You get a sheet for seals with exceptional flexibility and conduct to the court, which add to its characteristics swelling in control oil, its very appropriate for material industry in general.

Dimensions : 40X40, 50X50,60X62,75X75,60X120, 75X150, 150X150, 120X120 inches.

Thickness : 1/32, 3/64, 1/16, 3/32, 1/8, 3/16, ¼ inches and specials.

Compliant ASTM -F-104

PARAMETERS

AM 65

Service Pmax= 100 kg/cm² Tmax= 420°C



Manufacturera e Insumos, S.A. de C.V.
Camino viejo a la estación de FFCC No. 102.
Predio San Ignacio.
C.P. 38480.
Cortazar, Gto. México.
Tel. +52 (01411) 1553531.

THE DATA GIVEN ON THIS TECHNICAL SHEET SHOULD NOT BE USED AS APPLICATIONS LIMITS, BUT AS GUIDANCE FOR AN APPROPRIATE CHOICE. WE CAN OFFER GUARANTEES ONLY FOR THE QUALITY OF OUR PRODUCTS.

